

TRIGGAIR JLP FIBER BLOWING MACHINE

Robust handheld battery powered fiber blowing tool optimized for FTTX installation of blown fiber (EPFU) and micro/nano cables, from 0.8 to 3 mm into duct sizes 3, 5, 7 and 8 mm. The effective fiber security and adjustable clamping force ensure that all cable designs can be installed efficiently and safely. Equipped with Bluetooth for connection to an Android device running the JetLogger BT app. Delivered in a strong transport case with batteries, charger and an assortment of cable seals. Ready to blow!





FIBER BLOWING MACHINE FOR CABLE 0,8-3 MM / DUCT 3, 5, 7 AND 8 MM.

- Electrically operated. Battery connected.
- JetLogger prepared (via Bluetooth connection to Android devices)
- Fiber security by mechanical clutch and adjustable clamping force.
- Forward and reverse.
- Drive wheel with rubber rings secure a good and soft grip.
- Digital display showing speed and distance.
- Max. speed: 492 ft/min
- Max pushing force: 6.7 lbf
- Speed control with constant speed support.

DOWNLOAD APP

JETLOGGER BT APP

Download the Jetlogger software directly from the Jetting website and install it on your Android phone or tablet. Connect to TriggAir JLP via Bluetooth to monitor installation data in real time. The Jetlogger app can be used free of charge to view live installation data such as speed, distance, pushing force, and air pressure. To save, export, and share installation logs, a full license is required. The license can be purchased directly within the app.

TECHNICAL DATA

Battery:
12V, 4Ah Milwaukee

Min / Max pressure:
116–232 psi

Pushing force:
6.7 lbf

Cable diameter:
0,8 – 3 mm

Duct diameter:
3, 5, 7, 8 mm

Weight:
13.9 lb (transport box included)

Air connection:
Std 3/8" Cejn

WxHxD (transport box)
18.11 × 13.78 × 7.09 in



TRIGGAIR TRANSPORT CASE



JETLOGGER BT APP



CRUISE CONTROL



TABLE BRACKET



3-STEP DUCT ADAPTOR 5-7 AND 8 MM



TRIGGAIR WITH TRIPOD



METAL WHEEL FOR CABLE 2-3 MM



COMPRESSOR JETAIR 100270



12V, 4AH MILWAUKEE BATTERY



BATTERY CHARGER

STD CONFIGURATION

- TriggAIR machine
- 110/230 Charger for 12 V battery
- 2 pcs 12 V lithium battery with 4 Ah Milwaukee connector
- Cable Seal assortment:
  - 10 pcs 1,2 mm
  - 10 pcs 1,8 mm
  - 10 pcs 2,2 mm
  - 10 pcs 2,8 mm
- Original Jetting Duct cutter
- User manual

ACCESSORIES

- Reel arm for drum with fiber.
- Foldable tripod.
- Metal wheel for cable 2-3 mm.
- Table bracket. For safe installation on working table.
- Jetair 100270 Compressor
- JetLogger BT app

JETTING GUIDELINE FOR COMPRESSOR CAPACITY

DUCT/PIPE	AIR FLOW	AIR PRESSURE
Up to Ø 4 mm	3.5 CFM	116–232 psi
Ø 4–7 mm	5.3 CFM	116–232 psi
Ø 8–10 mm	10.6 CFM	116–232 psi
Ø 12–16 mm	21.2 CFM	116–232 psi